

WAAS CH <b>93833</b> <b>W35A</b>	APP CRS <b>353°</b>	Rwy Idg TDZE Apt Elev	<b>3200</b> <b>20</b> <b>20</b>
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 35


KIPNUK (IIK) (PAKI)

⚠

Baro-VNAV NA when using Toksook Bay altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). Helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. Procedure NA at night. VDP NA when using Toksook Bay altimeter setting. When local altimeter setting is not received use Toksook Bay altimeter setting: increase LPV DA to 389 feet and visibility all Cats ¼ SM. Increase LNAV/VNAV DA to 465 and visibility all Cats ⅓ SM. Increase all MDA 120 feet. Increase LNAV Cat C and D visibility to 1 ¼ SM, Circling Cat C to 2 SM, Cat D to 2 ¼ SM.

MISSED APPROACH: Climb to 500 then climbing right turn to 2400 direct ZERPU and hold.

AWOS-3P <b>118.325</b>	ANCHORAGE CENTER <b>125.2 372.0</b>	CTAF <b>122.7 0</b>
---------------------------	--	------------------------



4 NM Holding Pattern

2400 ← 173°  
353° →

GP 3.00°  
TCH 40

WOMSA

ZIVTO

RW35

\*1.4 NM to RW35

\*LNAV only

8 NM

3.8 NM

1.4 NM

CATEGORY	A	B	C	D
LPV DA	270-1 250 (300-1)			
LNAV/VNAV DA	346-1 326 (400-1)			
LNAV MDA	520-1	500 (500-1)	520-1 500 (500-1)	500 (500-1)
CIRCLING	580-1	560 (600-1)	580-1 560 (600-1)	580-2 560 (600-2)

ELEV 20

TDZE 20

353° to RW35

MIRL Rwy 17-35 0