

WAAS
CH **70642**
W22D

APP CRS
216°

Rwy Idg
TDZE **642**
Apt Elev **645**

RNAV (GPS) Z RWY 22R

DETROIT METROPOLITAN WAYNE COUNTY (DTW)

RNP APCH.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500.

MALSR

MISSED APPROACH: Climb to 1100 then dimbing right turn 4000 direct DOHNT and hold, continue climb in hold to 4000.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 128.125 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	---------------------------------------	---	---------------------------	-------

1100

4000

DOHNT

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/ TCH 71)

*LNAV only.

RW22R

GEETR

NUJNT

JOYDD

GUYVE

TARAH

FUDDJ

1 NM

3.1 NM

3.1 NM

3.1 NM

3.1 NM

3.1 NM

2.1 NM

2000

3000

3000

4000

4000

4000

4000

216°

4000

GP 3.00° TCH 55'

CATEGORY	A	B	C	D
LPV DA		842/18	200 (200-½)	
LNAV/ VNAV DA		948/24	306 (400-½)	
LNAV MDA	1040/24	398 (400-½)	1040/35	398 (400-⅝)
CIRCLING	1180-1	535 (600-1)	1180-1½ 535 (600-½)	1240-2 595 (600-2)

ELEV 645

D

TDZE 642

DETROIT, MICHIGAN

Orig-A 20JUN19

DETROIT METROPOLITAN WAYNE COUNTY (DTW)

42°13'N-83°21'W

RNAV (GPS) Z RWY 22R