

DAYTON, OHIO

## ILS or LOC RWY 23R

**LOC I-FFO 109.7** **APCH CRS 233°** **Rwy Idg 12,600** **THRE 823** **Arprt Elev 823** **AL-108 [USAF]** **WRIGHT-PATTERSON AFB (KFFO)**

**\*When ALS inop, increase RVR to 40 and vis to ¾ mile.**  
**\*\*When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1 ½ miles.**

**ALS-F-1** **† MISSED APPROACH: Climb via FFO R-233 to 2000, at 3 DME turn left direct CLACK to 3000 and hold.**

<b>ATIS</b> <b>124.475 269.9</b>	<b>COLUMBUS APP CON</b> <b>118.85 269.275</b>	<b>PATTERSON TOWER</b> <b>126.9 281.45</b>	<b>GND CON</b> <b>121.8 335.8</b>
-------------------------------------	--	---	--------------------------------------

**\*\*\* When Rwy 23R VGSi inop, circling to Rwy 23R NA at night.** **† Missed approach requires use of RNAV or ATC radar monitoring.**

**DME or RADAR REQUIRED FOR LOCALIZER**

**EMERG SAFE ALT 100 NM 3700**

CATEGORY	A	B	C	D	E
S-ILS 23R *	1023/24	200	(200-½)		
S-LOC 23R **	1320/24 497 (500-½)	1320/50	497 (500-1)		
CIRCLING ***	1380-1 557 (600-1)	1440-1 617 (600-1)	1560-2 737 (800-2)	1620-2½ 797 (800-2½)	1620-2¾ 797 (800-2¾)

**HIRL Rwy 5L-23R**  
**MIRL Rwy 5R-23L**