

LOC I-ILN 110.7	APP CRS 223°	Rwy Idg 10701 TDZE 1077 Apt Elev 1077
---------------------------	------------------------	--

ILS or LOC RWY 22R
WILMINGTON AIR PARK (ILN)

DME or RADAR required for procedure entry.
ADF or DME required for LOC only.

T Simultaneous approach authorized. VDP NAL with James M Cox Dayton IL altimeter setting. When local altimeter setting not received, use James M Cox Dayton IL altimeter setting: increase DA to 1367 feet and all visibilities to RVR 2200; increase all MDA 100 feet and S-LOC 22R visibility Cat C/D to RVR 4000 and Circling Cat C/D $\frac{1}{2}$ SM. For enroute ALS when using James M Cox Dayton IL altimeter setting, increase S-ILS 22R all Cats visibility to RVR 4500 and S-Loc 22R Cats C/D visibility to $\frac{1}{4}$ SM. DME from MXQ VOR/DME. Simultaneous reception of IJLN and MXQ DME required.

ALSF-2



MISSED APPROACH:
Climb to 1600 then
climbing right turn to
3500 on MXQ VOR/
DME R-250 to KLARC
INT/MXQ 10 DME/
RADAR and hold,
continue climb-in-hold
to 3500.

ATIS 124.925	COLUMBUS APP CON 118.85 269.275	WILMINGTON TOWER ★ 119.475 (CTAF) 0	GND CON 121.6	CLNC DEL 128.85
------------------------	---	---	-------------------------	---------------------------

