

LOC I-HUF <b>109.7</b>	APP CRS <b>049°</b>	Rwy Idg TDZE Apt Elev	<b>9020</b> <b>578</b> <b>589</b>
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 5  
TERRE HAUTE RGNL (HUF')

ADF or DME required.

**⚠** VDP NA when using Paris altimeter setting. When local altimeter setting not received, use Paris altimeter setting and increase all DA 61 feet and all MDA 80 feet, increase S-LOC 5 Cats C/D visibility to RVR 4500. For inop ALS, increase S-LOC 5 Cat C/D visibility to RVR 5500, when using Paris altimeter setting increase S-ILS 5 all Cats visibilities to RVR 4500 and S-LOC Rwy 5 all Cats visibility ½ SM. **\*\*RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Paris altimeter setting.**

**MALSR** **MISSED APPROACH:**  
Climb to 2300 direct  
TTH VORTAC and hold.

ATIS <b>127.5 269.375</b>	HULMAN APP CON <b>125.45 339.8</b>	HULMAN TOWER <b>134.725 239.0</b>	GND CON <b>121.6 348.6</b>
------------------------------	---------------------------------------	--------------------------------------	-------------------------------

