

WAAS
CH **86519**
W05A

APP CRS
053°

Rwy Idg
TDZE **1297**
Apt Elev **1297**

RNAV (GPS) RWY 5
MANSFIELD LAHM RGNL (MF'D)

RNP APCH

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F).

MISSED APPROACH: Climb to 3000 direct NANNI and hold.

ATIS
125.3

CLEVELAND APP CON ★
124.2 360.65

MANSFIELD TOWER ★
119.8 (CTAF) 291.775

GND CON
121.8 291.775

UNICOM
122.95

The main chart displays the RNAV (GPS) RWY 5 approach. It starts with a DUSKY VORTAC at 3000 feet, 120° bearing, 20.8 NM. The path proceeds through several waypoints: HUDOR (IAF), JOKAM (IF/IAF), ZOLEL (FAF), and WOVOM (2.3 NM to RW05). Key altitudes include 1853, 1564, 1647, 1799±, and 1952. The chart also shows a missed approach fix (NANNI) at 4 NM, a 4 NM holding pattern at JOKAM, and a 4 NM holding pattern at ZOLEL. A 3000-foot MSA (Minimum Safe Altitude) circle is centered on RW05 25 NM. The chart includes various navigation aids and symbols for terrain and obstructions.

4 NM Holding Pattern JOKAM

3000 ← 233° / 053° →

GP 3.00° TCH 50

2700

2060

6 NM | 2 NM | 0.8 NM | 1.5 NM

3000 NANNI

*LNAV only.

*1.5 NM to RW05

RW05

CATEGORY	A	B	C	D
LPV DA	1547-7/8		250 (300-7/8)	
LNAV/VNAV DA	1590-1		293 (300-1)	
LNAV MDA	1820-1 523 (600-1)		1820-1½ 523 (600-1½)	
CIRCLING	1820-1 523 (600-1)		2000-2 703 (800-2) 2000-2¼ 703 (800-2¼)	

ELEV 1297

D

TDZE 1297

9001 x 150

6819 x 150

TWR 1409

1354

053° to RW05

HIRL Rwy 5-23 and 14-32

REIL Rwy 5 and 23

MANSFIELD, OHIO
Amdt 1A 13SEP18

40°49'N-82°31'W

MANSFIELD LAHM RGNL (MF'D)
RNAV (GPS) RWY 5

EC-2, 03 DEC 2020 to 31 DEC 2020

EC-2, 03 DEC 2020 to 31 DEC 2020