

WAAS  
CH **72601**  
**W32A**

APP CRS  
**319°**


Rwy Idg  
TDZE  
Apt Elev  
**6500**  
**937**  
**937**

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Fort Wayne Intl altimeter setting. For inop MALSR when using Fort Wayne Intl altimeter setting, increase LPV all Cats visibility to 1½ mile. When local altimeter setting not received, use Fort Wayne Intl altimeter setting and increase DA 121 feet; increase LPV and LNAV/VNAV all Cats visibility by ½ mile; increase all MDA 140 feet and LNAV visibility Cats C and D to 1¼; increase Circling visibility Cats C and D by ¼ mile. For inop MALSR, increase all LPV Cats visibility to 1 SM.

MALSR



MISSED APPROACH:  
Climb to 2800 direct JOGBA and hold.

ATIS <b>133.25</b>	INDIANAPOLIS APP CON <b>120.65 317.8</b>	MUNCIE TOWER★ <b>120.1 (CTAF) 0</b>	GND CON <b>121.9</b>	UNICOM <b>122.95</b>
-----------------------	---	--	-------------------------	-------------------------

ELEV 937

**D**

TDZE 937

2800	JOGBA	5 NM Holding Pattern		
*LNAV only.	*1.2 NM to RW32	CITUK		
RW32	PEYIV 2600	2600		
1.2	3.8 NM	6 NM		
GP 3.04° TCH 52				
CATEGORY	A	B	C	D
LPV DA	1241-½	304 (400-½)		
LNAV/VNAV DA	1396-1⅛	459 (500-1⅛)		
LNAV MDA	1460-½ 523 (600-½)	1460-1 523 (600-1)		
CIRCLING	1460-1 523 (600-1)	1480-1½ 543 (600-1½)	1560-2 623 (700-2)	

MUNCIE, INDIANA  
Orig-B 12OCT17

40°15'N-85°24'W

DELAWARE COUNTY RGNL (MIE)  
**RNAV (GPS) RWY 32**