

WAAS CH 50107 W27A	APP CRS 274°	Rwy Idg TDZE 778 Apt Elev 778
--	------------------------	---

RNAV (GPS) RWY 27

ELKHART MUNI (EKM)

RNP APCH

When local altimeter setting not received, use South Bend altimeter setting: increase LPV DA to 1111 feet; increase LNAV/VNAV DA to 1261 feet; increase all MDA 40 feet and LNAV visibility Cat C/D to RVR 5500, Circling Cat D visibility ¼ SM. VDP and Baro-VNAV NA with South Bend altimeter setting. Circling Rwy 36 NA at night. Circling NA to Rwy 8 and 26. Rwy 27 helicopter visibility reduction below RVR 4000 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LPV all Cats visibility to RVR 4500, LNAV/VNAV all Cats visibility to 1½ SM, LNAV Cat A/B visibility to RVR 5500 and Cat C/D to 1½ SM. For inop ALS when using South Bend altimeter setting, increase LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cat A/B to RVR 5500

MALSR

MISSED APPROACH:
Climb to 4000 direct CIGIP and via 027° track to JJANN and hold.

AWOS-3 124.475	SOUTH BEND APP CON ★ 118.55 257.8	ELKHART TOWER ★ 119.5 (CTAF) 0	GND CON 121.8	CLNC DEL 121.8	UNICOM 122.95
--------------------------	---	--	-------------------------	--------------------------	-------------------------

