

ILS RWY 27C (SA CAT I)
CHICAGO O'HARE INTL (ORD)

MISSED APPROACH: Climb to 1100 then climbing right turn to 4000 on heading 290° and CGT R-322 to UKUNE INT/CGT 48 DME and hold.


CPDLC

Diagram illustrating the S-ILS 27C glidepath profile. The profile shows a 3D perspective of the glidepath starting at 1100 feet and descending to 2200 feet. Key features include:

- Initial climb: 1100 feet, heading 290 degrees.
- CGT R-322 and UKUNE INT.
- DRISCL INT I-UYJ [6.7] RADAR.
- JMBBO I-UYJ [12.7] RADAR.
- MRRFF I-UYJ [15.8] RADAR.
- BOOWW I-UYJ [18.9] RADAR.
- CERM I-UYJ [22.1] RADAR.
- CRICO I-UYJ [25.2] RADAR.
- NCHLS I-UYJ [28.4] RADAR.
- GS 3.00° TCH 56.
- Altitude markers: 4000, 3000, 2000, 1000, 500, 0.
- Distance markers: 4.7 NM, 6 NM, 3.1 NM, 3.1 NM, 3.1 NM, 3.1 NM, 3.1 NM.
- RA 158/14, 150 DA 803.

SA CATEGORY I ILS - SPECIAL AIRCREW
& AIRCRAFT CERTIFICATION REQUIRED

CHICAGO O'HARE INTL (ORD)
ILS RWY 27C (SA CAT I)