

ILS or LOC RWY 36  
GREEN BAY-AUSTIN STRAUBEL INTL (GRB)

**MISSED APPROACH:** Climb to 1400 then climbing left turn to 2500 direct GRB VORTAC and hold.

CLNC DEL  
**121.75**




Diagram illustrating the MAZTT FIX and associated navigation data:

- Initial heading: 1400 (upward arrow)
- Initial heading: 2500 (curved arrow)
- GRB (Ground Reference Beacon) symbol
- MAZTT INT (MAZTT Intersection)
- SG LOM (Signal Ground Line of Movement)
- 3100 (Distance/Heading)
- 2116 (Distance/Heading)
- 2200 (Distance/Heading)
- 1200 (Distance/Heading)
- 1.5 NM (Distance)
- 2.8 NM (Distance)
- Remain within 10 NM (Instruction)
- GS 3.00° TCH 50 (Glide Slope and Threshold Crossing Height)

CATEGORY	A	B	C	D
S-ILS 36	**884/24 200 (200-½)			
S-LOC 36	1200/24 516 (600-½)	1200/50 516 (600-1)	1200/60 516 (600-1¼)	
CIRCLING	1200-1 505 (600-1)	1200-1½ 505 (600-½)	1260-2 565 (600-2)	
MAZTT FIX MINIMUMS				
S-LOC 36	980/24 296 (300-½)	980/40 296 (300-¾)		
CIRCLING	1200-1 505 (600-1)	1200-1½ 505 (600-½)	1260-2 565 (600-2)	