

WAAS
CH **49105**
W33A

APP CRS
328°

Rwy Idg
TDZE **705**
Apt Elev **712**

RNAV (GPS) RWY 33
AURORA MUNI (ARR)

RNP APCH.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.
For inop MALS, increase LPV visibility to 1¼ SM all Cts, LNAV Cts A/B visibility to 1 SM.

MALS

AS

MISSED APPROACH:
Climb to 3000 direct
UCORO and hold,
continue climb-in-hold
to 3000.

ATIS
125.85

CHICAGO APP CON
133.5 349.0

AURORA TOWER ★
120.6 (CTAF) 0

GND CON
121.7

CLNC DEL
121.7
(When tower closed)

UNICOM
122.95 123.5

ELEV **712**

TDZE **705**

Procedure NA for arrival on JOT VOR/DME
airway radials 314 CW 328.

3000 UCORO

↑

✧

*LNAV only.

RW33

328° to RW33

RIESR

2300

BOBBB

2600

JOT VOR/DME

346°

2600

GP 3.00°

TCH 48

1.3 NM

3.5 NM

6 NM

4.4 NM

CATEGORY	A	B	C	D
LPV DA	1042-¾	337 (400-¾)		
LNAV/VNAV DA	1194-1¼	489 (500-1¼)		
LNAV MDA	1140-¾	435 (500-¾)		1140-1 435 (500-1)
CIRCLING	1200-1	488 (500-1)	1200-1½ 488 (500-1½)	1320-2 608 (700-2)

HIRL Rwy 15-33 and 9-27

MIRL Rwy 18-36

REIL Rwy 15, 18, 27, and 36

CHICAGO/AURORA, ILLINOIS

Amdt 1A 13SEP18

41°46'N-88°29'W

AURORA MUNI (ARR)

RNAV (GPS) RWY 33