GATEWAY ONE DEPARTURE

(GATWY1.TWILA) 08NOV18

CAHOKIA/ST. LOUIS, ILLINOIS

ST LOUIS DOWNTOWN (CPS)

ATIS
121.45
CLNC DEL
118.275
121.8 (when tower closed)
GND CON
121.8
DOWNTOWN TOWER ★
119.925 379.3
ST LOUIS DEP CON
123.7 371.875

TOP ALTITUDE: ASSIGNED BY ATC

TAKEOFF MINIMUMS
Rwys 12L/R, 23, 30R: Standard.
Rwy 5: 200-1¼ or standard with minimum climb of 343′ per NM to 700.
Rwy 30L: 400-2½ or standard with minimum climb of 220′ per NM to 900, or alternatively, with standard takeoff minimums and a normal 200′ per NM climb gradient, takeoff must occur no later than 2100′ prior to DER.

BRICKYARD
116.3 VHP
Chan 110
N39°48.88′-W86°22.05′
L-27, H-5-10

ROSEWOOD
117.5 ROD
Chan 122
N40°17.27′-W84°02.59′
L-27, H-10

TERRE HAUTE
115.3 TTH
Chan 100

ST.LOUIS
117.4 STL
Chan 121
N38°51.64′-W90°28.94′

BIBLE GROVE
109.0 BIB
Chan 27
N38°55.22′-W88°28.91′
L-27, H-5

SHELBYVILLE
112.0 SHB
Chan 57
N39°37.95′
W85°49.46′

CREEP
N39°55.25′
W84°18.52′
H-10

KELLY
N39°24.82′
W86°40.28′

WORKE
N39°07.05′
W87°46.42′

JIGSY
N38°50.53′
W89°07.18′
L-27, H-5

TWILA
N38°47.23′
W89°33.15′

CENTRALIA
115.0 ENL
Chan 97

TROY
116.0 TOY
Chan 107
N38°44.35′-W89°55.12′

094° (44)
076° (17)
076° (21)
078° (30)
067° (35)
071° (41)
063° (91)
075° (72)
029° (28)
R-097 61
(54)
R-209
R-085
R-250
R-214
R-251
R-258
R-090
R-316
R-360
FL180 *2600
3800 *2300
3000 *2300
3000 *2000
3800 *2200
3800 *2600
V12
V11
STL
38
70
1600
900
1000
2000
047°
122°
227°
302°

NOTE: RADAR required.
NOTE: BRICKYARD transition, CREEP transition, and ROSEWOOD transition: DME required.

N

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

(GATWY1.TWILA) 20086

GATEWAY ONE DEPARTURE

AL-5316 (FAA)

ST LOUIS DOWNTOWN (CPS)

CAHOKIA/ST. LOUIS, ILLINOIS