WAAS	APP CRS	Rwy Idg	5500
CH 77731	018°	TDZE	1018
W02A		Apt Elev	1021

RNAV (GPS) RWY 2

ALEXANDER FIELD SOUTH WOOD COUNTY (ISW)

RNP APCH.

Circling NA to Rwys 18 and 36. Circling Rwy 20, 30 NA at night. Baro-VNAV and VDP NA when using Stevens Point altimeter setting. Rwy 2 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Stevens Point altimeter setting; increase LPV DA to 1351 feet; increase LNAV/VNAV DA to 1546 feet and all visibilities ⅛ SM; increase all MDAs 60 feet, LNAV Cat C and D visibilities ⅛ SM and Circling Cat C and D visibilities ¼ SM.

MISSED APPROACH: Climb to 3000 direct UYOLU and on track 022° to AKAKE and hold.

ASOS	MINNEAPOLIS CENTER	UNICOM
126.575	124.4 317.7	122.8 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	1298-1	280 (300-1)		
LNAV/VNAV DA	1493-1⅜	475 (500-1⅜)		
LNAV MDA	1440-1	422 (500-1)	1440-1¼	422 (500-1¼)
C CIRCLING	1480-1 459 (500-1)	1560-1 539 (600-1)	1620-1½ 599 (600-1½)	1800-2½ 779 (800-2½)

ELEV 1021 TDZE 1018



REIL Rwys 2 and 20 L
MIRL Rwys 2-20 and 12-30 L

EC-3, 03 DEC 2020 to 31 DEC 2020
EC-3, 03 DEC 2020 to 31 DEC 2020