

AWOS-3  
120.0  
CLNC DEL  
124.75  
MILWAUKEE DEP CON  
125.35 307.0



**TOP ALTITUDE:  
ASSIGNED BY ATC**

## TAKEOFF MINIMUMS

Rwy 6: Standard.

Rwy 13: 300-1½ or standard with minimum climb of 260' per NM to 1200.

Rwy 24: 300-2 or standard with minimum climb of 250' per NM to 1400.

Rwy 31: 300-1¼ or standard with minimum climb of 220' per NM to 1100.


NOTE: RNAV 1.

NOTE: GPS or DME/DME/IRU required.

NOTE: RADAR required.

NOTE: Turbojet aircraft maintain 250K until advised by ATC.

NOTE: Notify ATC if unable to comply with crossing restrictions.



NOTE: Chart not to scale.



## DEPARTURE ROUTE DESCRIPTION

Climb on assigned heading for RADAR vectors to PRFEC, thence....

...on track 181° to cross OZAUZ at or above 11000, then on track 181° to cross MAULT at or above 13000, then on track 193° to cross UECKR at or above 16000, then on (transition). Maintain ATC assigned altitude, expect filed altitude ten minutes after departure.

DELHI TRANSITION (UECKR6.DELHI)

## SAMPL TRANSITION (UECKR6.SAMPL)