

APP CRS
301°

Rwy Idg
5000

TDZE
1070

Apt Elev
1086

RNAV (GPS) RWY 30

MONROE MUNI (EFT)

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Albeturs altimeter setting and increase all MDA 100 feet, increase LNAV Cat C/D and Circling Cat C visibility ¼ mile. VDP NA when using Albeturs altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climbing left turn to 3000
direct DAVIS and hold.

AWOS-3 118.375	ROCKFORD APP CON 126.0 327.0	UNICOM 123.05 (CTAF) 0
--------------------------	--	----------------------------------

ELEV 1086 TDZE 1070

MIRL Rwy's 12-30 and 2-20
REIL Rwy's 2, 12, 20, and 30

3000 DAVIS		XOTIY 3000		
ZEBRU 2700		Procedure Turn NA		
1.2 NM to RW30		3.04° TCH 42		
1.2		3.8 NM		
6.2 NM				
CATEGORY	A	B	C	D
LNAV MDA	1480-1	410 (400-1)	1480-1¼	410 (400-1¼)
CIRCLING	1540-1 454 (500-1)	1640-1 554 (600-1)	1640-1½ 554 (600-1½)	1640-2 554 (600-2)

MONROE, WISCONSIN

42°37'N-89°35'W

MONROE MUNI (EFT)

RNAV (GPS) RWY 30