

WAAS CH 58109 W02A	APP CRS 021°	Rwy Idg TDZE 913 Apt Elev 914	7026 913 914
--	------------------------	---	---


RNAV (GPS) RWY 2
DE KALB TAYLOR MUNI (DKB)

▼ Baro-VNAV NA when using Aurora altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. VDP NA when using Aurora altimeter setting. When local altimeter setting not received, use Aurora altimeter setting and increase all DA 61 feet and all MDA 80 feet; increase all LPV and LNAV/VNAV visibilities, LNAV Cats C/D visibility, and Circling Cats C/D visibility ¼ mile. For inop MALSR, increase LPV all Cats visibility to 1.

MALSR

MISSED APPROACH:
Climb to 3000 direct JUDVI and via 057° track to YEARN and hold.

AWOS-3 119.075	CHICAGO APP CON 133.5 349.0	UNICOM 122.7 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------



Procedure Turn NA				
<div><div>TUGBY</div><div>JINYO</div><div>VIIYUD 2.6 NM to RW02</div><div>JUDVI</div><div>YEARN</div></div>				
<div><div>2700</div><div>021°</div><div>2700</div><div>*1800</div><div>*1.2 NM to RW02</div><div>*LNAV only.</div></div>				
<div><div>GP 3.00°</div><div>TCH 55</div><div>6.1 NM</div><div>2.8 NM</div><div>1.4 NM</div><div>1.2 NM</div></div>				
CATEGORY	A	B	C	D
LPV DA	1207-½		294 (300-½)	
LNAV/VNAV DA	1360-1		447 (500-1)	
LNAV MDA	1360-½	447 (500-½)	1360-¾ 447 (500-¾)	1360-1 447 (500-1)
CIRCLING	1360-1 446 (500-1)	1480-1 566 (600-1)	1540-1¾ 626 (700-1¾)	1540-2 626 (700-2)

