

WAAS CH <b>40329</b> <b>W30A</b>	APP CRS <b>300°</b>	Rwy Idg <b>5199</b> TDZE <b>656</b> Apt Elev <b>656</b>
--	------------------------	---

## RNAV (GPS) RWY 30

WINONA MUNI-MAX CONRAD FIELD (ONA)



For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP 0.3 NA. When local altimeter setting not received, use the Crosse altimeter setting and increase all LPV DA to 1064 feet and visibility ½ mile all Cats, all LNAV/VNAV DA to 1193 and visibility ½ mile all Cats, and all MDA 60 feet, increase LNAV Cat C/D and Circling Cat B visibility ½ mile. For Inop ALS, increase LPV all Cats visibility to 1 ½ mile. For Inop ALS when using La Crosse altimeter setting, increase LPV all Cats visibility to 1 ½ mile, and LNAV Cats C/D visibility to 2 mile. Baro-VNAV and VDP NA when using La Crosse altimeter setting.

MALSR



**MISSED APPROACH:**  
Climb to 1800 then  
climbing right turn to  
3500 direct ALEYU and  
hold.

AWOS-3  
118.075

MINNEAPOLIS CENTER  
128.6 363.0

UNICOM  
122.8 (CTAF) **L**