WAAS	APP CRS	Rwy Idg	6401
CH 78314	131°	TDZE	1470
W13A		Apt Elev	1470

RNAV (GPS) RWY 13

DEVILS LAKE RGNL (DVL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Cando altimeter setting. When local altimeter setting not received, use Cando altimeter setting and increase all DA 63 feet and all MDA 80 feet, increase LPV and LNAV/VNAV all Cats visibility ¼ mile, LNAV and Circling Cats C and D visibility ¼ mile.

MISSED APPROACH: Climb to 3400 direct GRETE and hold.

AWOS-3PT	MINNEAPOLIS CENTER	UNICOM
125.875	124.2 270.3	122.8 (CTAF) L



ELEV 1470 D TDZE 1470



CATEGORY	A	B	C	D
LPV DA	1720-¾	250 (300-¾)		
LNAV/VNAV DA	1791-1	321 (400-1)		
LNAV MDA	1820-1	350 (400-1)		
C CIRCLING	2000-1	530 (600-1)	2240-2¼ 770 (800-2¼)	2240-2½ 770 (800-2½)



NC-1, 03 DEC 2020 to 31 DEC 2020
NC-1, 03 DEC 2020 to 31 DEC 2020