

APP CRS  
271°

Rwy Idg  
TDZE  
Apt Elev

5010  
777  
778

RNAV (GPS) RWY 27

RED WING RGNL (RGK)

▼

▲

DME/DME RNP-0.3 NA. VDP NA with South St. Paul altimeter setting. When local altimeter setting not received, use South St. Paul altimeter setting; increase all MDA 80 feet and LNAV Cat C visibility ½ mile, Circling Cat A and C visibility ¼ mile. Helicopter visibility reduction below ¾ SM NA. Inop table does not apply to LNAV Cat C.

ODALS

MISSED APPROACH:  
Climb to 3000 direct  
JUGAN and hold.

AWOS-3 119.25	MINNEAPOLIS APP CON 121.2 335.65	UNICOM 123.05 (CTAF) 0
------------------	-------------------------------------	---------------------------

ELEV 778

TDZE 777

3000

JUGAN

WETUG

2.7 NM to RW27

SIFRT

2.7 NM to RW27

ZAMLU

4 NM Holding Pattern

2.1 NM

0.6 NM

2.4 NM

6.9 NM

CATEGORY

A

B

C

D

LNAV MDA

1520-¾  
743 (800-¾)

1520-1¼  
743 (800-1¼)

1520-2  
743 (800-2)

NA

CIRCLING

1520-1  
742 (800-1)

1520-1¼  
742 (800-1¼)

1540-2¼  
762 (800-2¼)

NA

RED WING, MINNESOTA

Amdt 2C 10JAN13

44°35'N-92°29'W

RED WING RGNL (RGK)

RNAV (GPS) RWY 27