

WAAS
CH **73005**
W12A

APP CRS
126°

Rwy Idg **8279**
TDZE **3963**
Apt Elev **3967**

RNAV (GPS) RWY 12

WESTERN NEBRASKA RGNL/WILLIAM B HEILIG FIELD (BTF)

When local altimeter setting not received, use Alliance altimeter setting and increase all DAs 91 feet and all MDAs 100 feet; increase LPV, LNAV/VNAV, LNAV Cat A/B and Circling Cat B visibilities ¼ mile; increase LNAV and Circling Cat C/D visibilities ½ mile. For inoperative MALSR, when using Alliance altimeter setting, increase LPV all Cats visibility to 1¼, and LNAV Cat A visibility to 1. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 41°C (105°F). Baro-VNAV NA when using Alliance altimeter setting. VDP NA when using Alliance altimeter setting. DME/DME RNP-0.3 NA.

MALSR

MISSED APPROACH:
Climb to 6700 direct HAKAB and hold.

ASOS 121.025	DENVER CENTER 127.95 338.2	UNICOM 123.0 (CTAF) 1
------------------------	--------------------------------------	---------------------------------

Procedure NA for arrivals at ALBIN V81 southwest bound and arrivals at SPONS V81-V169 northbound.

ELEV 3967 D TDZE 3963

126° to RWY 12

8002 X 150

8279 X 150

4006

7 NM Holding Pattern

LEDSE

CAPGA

RWY 12

GP 3.00° TCH 57

6.1 NM

3.1 NM

2.1 NM

6700 HAKAB

*LNAV only

*2.1 NM to RWY 12

CATEGORY	A	B	C	D
LPV DA	4213-½ 250 (300-½)			
LNAV/VNAV DA	4340-¾ 377 (400-¾)			
LNAV MDA	4700-½ 737 (800-½)	4700-1½ 737 (800-1½)	4700-1¾ 737 (800-1¾)	4700-2 737 (800-2)
CIRCLING	4700-1 733 (800-1)	4700-2 733 (800-2)	4740-2½ 773 (800-2½)	

SCOTTSBLUFF, NEBRASKA
Amdt 1A 30JAN20

WESTERN NEBRASKA RGNL/WILLIAM B HEILIG FIELD (BTF)
41°52'N-103°36' W

RNAV (GPS) RWY 12