

LOC I-CDR 110.9	APP CRS 028°	Rwy ldg 5211 TDZE 3294 Apt Elev 3298
---------------------------	------------------------	--

ILS or LOC RWY 3

CHADRON MUNI (CDR)

ADF required. When local altimeter setting not received, use Pine Ridge altimeter setting and increase all DA 70 feet and all MDA 80 feet; increase S-LOC 3 Cats B/C/D visibility ¼ mile, Circling Cat B visibility ¼ mile and Cat C visibility ⅜ mile and Cat D visibility ½ mile. For inop MALSRS increase S-LOC 3 Cats C and D visibility to 1 ⅜ mile. For inop MALSRS when using Pine Ridge altimeter setting increase S-ILS 3 all Cats visibility to ⅞ mile and S-LOC 3 Cats C and D visibility to 2 miles.

MALSRS

MISSED APPROACH:
Climb to 5100 then climbing right turn to 6200 direct DAWES LOM and hold.

ASOS 118.05	DENVER CENTER 127.95 338.2	UNICOM 122.8 (CTAF) 0
-----------------------	--------------------------------------	---------------------------------

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 61).

Remain within 10 NM

GS 3.00° TCH 60

CD LOM DAWES

5100 6200 CD

5700 5500

1.6 NM 5.8 NM

028° 5.8 NM from FAF

CATEGORY	A	B	C	D
S-ILS 3	3494-½ 200 (200-½)			
S-LOC 3	3960-½ 666 (700-½)		3960-1½ 666 (700-1½)	
CIRCLING	3960-1 662 (700-1)		3960-2 662 (700-2)	

FAF to MAP 5.8 NM

Knots	60	90	120	150	180
Min:Sec	5:48	3:52	2:54	2:19	1:56

CHADRON, NEBRASKA
Amdt 2C 04FEB16

42°50'N-103°06'W

CHADRON MUNI (CDR)
ILS or LOC RWY 3