

RNAV (GPS) Z RWY 5
NORFOLK INTL (ORF)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C or above 54°C.
A For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cats C and D visibility to RVR 6000. **RVR 1800 authorized with use of FD or AP or HUD to DA.



MISSED APPROACH:
Climb to 2000 direct
TECH1 then on track 023°
to OUTLA and hold.

Procedure NA for arrivals at WAKS on V189-260 north bound.

(IAF) WAKS

3500 127° (39.3)

1282 Δ Δ 1245

173 Δ 173 Δ 177 \pm Δ 228

(FAF) CROOM 555 Δ 538 511

(IAF) CALEY

1200 047° (7.6)

Procedure NA for arrivals at DRONE on V1 southwest bound and V266 northwest bound.

(IAF) DRONE

3500 060° (20.1)

3500 027° (9.1)

(IAF) ARDEB

3500 342° (22.6)

ELIZABETH CITY ECG

Procedure NA for arrival on ECG VOR/DME airway radials 265 CW 311.

MISSED APCH FIX

OUTLA

4 NM

209° 029°

TECHI

023° (22.5)

MSA RW05 25 NM

2300

ELEV 27	D	TDZE 26
---------	---	---------

NORFOLK, VIRGINIA
Amdt 2A 10OCT19

36°54'N-76°12'W

NORFOLK INTL (ORF)
RNAV (GPS) Z RWY 5