

LOM SH
375

APP CRS
047°

Rwy Idg
TDZE
Apt Elev
6002
1184
1201

AL-5369 (FAA)

SHENANDOAH VALLEY RGNL (SHD)

NDB RWY 5

⚠

When local altimeter setting not received, use Charlottesville altimeter setting: increase all MDAs 140 feet and visibility S-5 and Circling Cat C/D ½ mile.

MALSR

MISSED APPROACH: Climb to 2400 then climbing left turn to 3600 direct SH LOM and hold.

AWOS-3 124.925	POTOMAC APP CON 132.85 323.125	CLNC DEL 118.35	UNICOM 123.0 (CTAF) 0
--------------------------	--	---------------------------	---------------------------------

Remain within 10 NM

SH LOM 6000

227°

047°

3700

2800

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 56).

3.50° TCH 60

4.2 NM

CATEGORY	A	B	C	D
S-5	1760-¾ 576 (600-¾)		1760-1 576 (600-1)	1760-1½ 576 (600-1½)
CIRCLING	1760-1 559 (600-1)		1760-1½ 559 (600-1½)	1820-2 619 (700-2)

ELEV 1201 D TDZE 1184

REIL Rwy 23 0

HIRL Rwy 5-23 0

1246

6002 X 150

0.4% UP

047° 4.2 NM from FAF

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

STAUNTON-WAYNESBORO-HARRISONBURG, VIRGINIA

SHENANDOAH VALLEY RGNL (SHD)

Amdt 10 27AUG09

38°16'N-78°54'W

NDB RWY 5