

WAAS CH 63202 W16A	APP CRS 164°	Rwy Idg 11901 TDZE 432 Apt Elev 432
--	------------------------	--

RNAV (GPS) Y RWY 16L
SEATTLE-TACOMA INTL (SEA)

RNP APCH.		<div>ALS-2</div> <div><div>A</div><div><div></div><div></div><div></div></div></div>	MISSED APPROACH: Climb direct CAYOBA to cross CAYOBA at or below 2000 then climb to 5000 on track 164° to MILIT and hold, continue climb-in-hold to 5000.			
<div><div></div><div>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 16R. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. For inop ALS, increase LPV all Cats visibility to RVR 4500, and increase LNAV Cats C/D visibility to RVR 6000.</div></div>						
D-ATIS	SEATTLE APP CON	SEATTLE TOWER		GND CON	CLNC DEL	CPDLC
118.0	133.65 273.45	119.9 239.3 (Rwys 16L, 16C, 34C, 34R) 120.95 239.3 (Rwys 16R, 34L)		121.7	128.0	

