RNAV (RNP) RWY 20

GLACIER PARK INTL (GPI)

APP CRS	Rwy Idg	9007
200°	TDZE	2977
	Apt Elev	2977

RF and GPS required. For uncompensated Baro-VNAV systems, procedure NA below -21°C (-5°F) or above 43°C (109°F). Visibility reduction by helicopters NA. -15°C *Missed approach requires minimum climb of 235 feet per NM to 6900.

MISSED APPROACH: Climb to 10000 via 200° track to CAUGH and via left turn to DOTRE, and via 128° track to ANGIL and hold, continue climb-in-hold to 10000.

ATIS	SALT LAKE CENTER	GLACIER TOWER *	GND CON	UNICOM
132.625	133.4 285.4	124.55 (CTAF) L	121.6	122.95



ELEV 2977	D	TDZE 2977



REIL Rwy 20 L
MIRL Rwy 12-30 L
HIRL Rwy 2-20 L



CATEGORY	A	B	C	D
RNP 0.10 DA*	3344-1¼ 367 (400-1¼)			
RNP 0.30 DA*	3446-1¾ 469 (500-1¾)			
RNP 0.30 DA	3662-2½ 685 (700-2½)			

AUTHORIZATION REQUIRED

NW-1, 03 DEC 2020 to 31 DEC 2020
NW-1, 03 DEC 2020 to 31 DEC 2020