

APP CRS 063°	Rwy Idg	10014
	TDZE	258
	Apt Elev	298

RNAV (RNP) Z RWY 6R

GUAM INTL (GUM)(PGUM)

▼

For uncompensated Baro-VNAV systems, procedure NA below 19°C (66°F) or above 48°C (119°F). GPS required.
*Missed approach requires a minimum climb of 285 feet per NM to 1400.

MALSR

MISSED APPROACH:

Climb to 3000 via track 063° to CIBOL and hold.

ATIS 119.0	GUAM CERAP 119.8 269.0	AGANA TOWER 118.1 340.2	GND CON 121.9 336.4	CLNC DEL 121.9
----------------------	----------------------------------	-----------------------------------	-------------------------------	--------------------------

WUVEN 16000
3000
164°
(35.9)

Procedure NA for arrivals at WUVEN via A597 northwest bound.

Procedure NA for arrivals at PULEE via G467 R596 westbound.

(IAF) PULEE 13300
3000
102°
(32.7)

(IF) DALPE
3000
153°
(5.1)

(IAF) RASPE 4600 210K
3000
153°
(5.3)

(FAF) FISON 724
2000
063°
(7)

1190
063°
(5.3)

Λ 412
Λ 812
Λ 412

RW06R

MISSED APCH FIX
4 NM
063°
243°
CIBOL

MSA RW06R 25 NM
2600

• 1332

(IAF) BURLE 6100
3000
333°
(9.9)

3000
333°
(9.9)

Procedure NA for arrivals at ASADE via B586 southeast bound.

ASADE 15100
3000
337°
(28.6)

Procedure Turn NA

DALPE

3000

063°

2000

FISON

3000

CIBOL

GP 3.00°
TCH 55

7 NM

5.3 NM

CATEGORY	A	B	C	D
RNP 0.30* DA		508-½	250 (300-½)	
RNP 0.30 DA		656-1	398 (400-1)	

AUTHORIZATION REQUIRED

ELEV 298 D TDZE 258

341±
0.5% UP
0.7% DOWN
12017 X 150
10014 X 150
0.8% UP
0.6% DOWN
270±
063° to RW06R
TWR 352
554
HIRL all Rwy's

GUAM, GU

Orig-C 15DEC11

13°29'N-144°48'E

GUAM INTL (GUM)(PGUM)

RNAV (RNP) Z RWY 6R