

▼

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Wiley Post altimeter setting and increase all DA 29 feet and all MDA 40 feet and increase LPV all Cats visibility ¼ mile. VDP NA when using Wiley Post altimeter setting.

⚠

MISSED APPROACH: Climb to 3800 direct JEBGO and hold.

AWOS-3 125.05	OKE CITY APP CON 124.6 266.8	UNICOM 123.0 (CTAF) 0
------------------	---------------------------------	--------------------------

4 NM Holding Pattern		VGSI and RNAV glidepath not coincident.		3800	JEBGO	
GP 3.00° TCH 52		CATKI		BLAZO	HESVA	
3800		3000		RWY 17R		
6.1 NM		1.9 NM		2 NM		
1.1 NM		1.1 NM		1.1 NM		
CATEGORY	A	B	C	D		
LPV DA	1601-¾ 250 (300-¾)			NA		
LNAV MDA	1760-1	409 (500-1)	1760-1¼ 409 (500-1¼)	NA		
CIRCLING	1800-1 446 (500-1)	1820-1 466 (500-1)	1820-1½ 466 (500-1½)	NA		

ELEV 1354

TDZE 1351

173° to RWY 17R

17R

17L

35L

35R

601.4 x 100

3502 x 75

MIRL Rwy 17L-35R

HIRL Rwy 17R-35L

OKLAHOMA CITY, OKLAHOMA

Amdt 2A 13DEC12

35°29'N-97°49'W

CLARENCE E PAGE MUNI (R/C/E)

RNAV (GPS) RWY 17R