

LOC/DME I-PNC  
**111.9**  
Chan **56**

APP CRS  
**175°**

Rwy Idg  
TDZE  
Apt Elev  
**7201**  
**1004**  
**1008**

ILS or LOC/DME RWY 17

PONCA CITY RGNL (PNC)

When local altimeter setting not received, use Winfield-Arkansas City altimeter setting and increase S-ILS 17 DA 82 feet and all MDA 100 feet; increase S-LOC Cat C and D and Circling Cat C visibility ¼ mile. For inop MALS, when using Winfield-Arkansas City altimeter setting, increase S-ILS 17 visibility to 1 mile all Cats. VDP NA when using Winfield-Arkansas City altimeter setting.

MALS  
A5

MISSED APPROACH:  
Climb to 2500 then climbing right turn to 2700 direct PER VORTAC and hold.

ASOS  
**134.075**

KANSAS CITY CENTER  
**127.8 319.1**

UNICOM  
**123.0 (CTAF)**

MSA PER 25 NM  
3200

ALTERNATE MISSED APCH FIX  
LOM PONCA  
PN 515

One Minute Holding Pattern

2700

355°

175°

2700

GS 3.00°

TCH 48

ELEV 1008

TDZE 1004

175° 5.1 NM from FAF

2500

2700

PER

2700

PER

2700

PER

CATEGORY	A	B	C	D
S-ILS 17		1204-½	200 (200-½)	
S-LOC 17	1520-½	516 (600-½)	1520-1	1520-1¼
			516 (600-1)	516 (600-1¼)
CIRCLING	1520-1	512 (600-1)	1560-1½	1560-2
			552 (600-1½)	552 (600-2)

HIRL Rwy 17-35

PONCA CITY, OKLAHOMA

Amdt 3 25SEP08

36°44'N-97°06'W

PONCA CITY RGNL (PNC)

ILS or LOC/DME RWY 17