

RADAR INSTRUMENT APPROACH MINIMUMS

ABILENE, TX

Amdt 10, 05JAN17 (17005) (FAA)

ELEV 1791

ABILENE RGNL (ABI)

RADAR-1 125.0 338.3 (EAST), 127.2 282.3 (WEST)

	RWY	GP/TCH/RPI	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS
ASR	17R		AB	2240-1	469	(500-1)	CDE	2240-1 $\frac{3}{4}$	469	(500-1 $\frac{3}{4}$)
	35R		AB	2340- $\frac{1}{2}$	564	(600- $\frac{1}{2}$)	CDE	2340-1 $\frac{1}{4}$	564	(600-1 $\frac{1}{4}$)
	35L		AB	2340-1	553	(600-1)	CDE	2340-1 $\frac{1}{4}$	553	(600-1 $\frac{1}{4}$)
CIRCLING	ALL RWY		AB	2340-1	549	(600-1)	C	2420-1 $\frac{3}{4}$	629	(700-1 $\frac{1}{2}$)
			D	2460-2	669	(700-2)	E	2620-3	829	(900-2)

When control tower closed, ASR NA.
For inoperative ALS, increase ASR-35R CAT E visibility to 1 $\frac{1}{2}$ SM.

AMARILLO, TX

Amdt 16, 25MAR99 (99084) (FAA)

ELEV 3605

RICK HUSBAND AMARILLO INTL (AMA)

RADAR-1 119.5 307.0

	RWY	GP/TCH/RPI	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS
ASR	22		ABC	3960- $\frac{3}{4}$	357	(400- $\frac{3}{4}$)	DE	3960-1 $\frac{1}{4}$	357	(400-1 $\frac{1}{4}$)
	31		ABC	3960-1	362	(400-1)	D	3960-1 $\frac{1}{4}$	362	(400-1 $\frac{1}{4}$)
			E	NA						
	13		ABC	3980-1	380	(400-1)	D	3980-1 $\frac{1}{4}$	380	(400-1 $\frac{1}{4}$)
			E	NA						
	4		AB	4160/24	555	(600- $\frac{1}{2}$)	C	4160/50	555	(600-1)
			D	4160/60	555	(600-1 $\frac{1}{4}$)	E	4160-1 $\frac{1}{2}$	555	(600-1 $\frac{1}{2}$)
CIRCLING	ALL RWY		AB	4160-1	555	(600-1)	C	4160-1 $\frac{1}{2}$	555	(600-1 $\frac{1}{2}$)
			D	4240-2	635	(700-2)	E	4460-3	855	(900-3)

When control tower closed, procedure not authorized.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

DYESS AFB (KDYS), TX (Abilene) (Amdt 3, 15344 USAF)

ELEV 1790

RADAR - (E) 121.3 127.2 270.3 282.3

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATh/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	34 ¹		AB	2260/24	472	(500-½)
			CDE	2260/50	472	(500-1)
	16 ¹		AB	2300/24	510	(600-½)
			CDE	2300/55	510	(600-1)
C CIR	16 ²		A	2300-1	510	(600-1)
			B	2320-1¼	530	(600-1¼)
			C	2460-1¾	670	(700-1¾)
			D	2460-2	670	(700-2)
			E	2460-2¼	670	(700-2¼)
	34 ³		A	2300-1	510	(600-1)
			B	2320-1	530	(600-1)
			C	2460-1¾	670	(700-1¾)
			D	2460-2	670	(700-2)
			E	2460-2¼	670	(700-2¼)

¹When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1¾ miles.

²Circling to other than Rwy 34 NA.

³Circling to other than Rwy 16 NA.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

FORT WORTH NAS JRB (CARSWELL FLD) (NFW), Fort Worth, TX
18JUN20 (20170) (USN)
RADAR - (E)¹ 128.775 371.875 

ELEV 650

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR ²	36 ⁴	3.0°/59/1226	ABCDE	850-½	200	(200-½)
	18 ^{3,7}	3.0°/61/1071	ABCDE	836-¾	200	(200-¾)
PAR W/O GS ²	18		AB	1040-1	404	(400-1)
			CDE	1040-1⅙	404	(400-1⅙)
	36 ^{5,10}		AB	1160-½	510	(600-½)
			CDE	1160-1	510	(600-1)
ASR ²	18 ⁹		AB	1120-1¼	484	(500-1¼)
			CDE	1120-1⅜	484	(500-1⅜)
	36 ⁶		AB	1220-¾	570	(600-¾)
			CDE	1220-1¼	570	(600-1¼)
CIR	18-36 ⁸		A	1240-1¼	590	(600-1¼)
			B	1280-1¼	630	(700-1¼)
			C	1320-1¼	670	(700-1¼)
			D	1320-2	670	(700-2)
			E	1320-2¼	790	(800-2¾)

¹Opr 1300-0500Z++ Mon-Fri; clsd Sat, Sun and hol. Afld hr subject to chg by NOTAM. Base OPS/ATC not manned outside of publ hrs.

²No-NOTAM MP: PAR 1230-1530Z++ Tue, Thu; ASR 1230-1530Z++ Mon, Wed.

³CAUTION: PAR TCH exceeds 60'.

⁴When ALS inop, increase vis to ¾ mile.

⁵When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1⅙ miles.

⁶When ALS inop, increase CAT AB vis to 1¼ miles, CAT CDE vis to 1⅙ miles.

⁷CAUTION: WCH for Height Group 1 (53 ft) is higher than the maximum 50 ft. WCH Group 1 includes general aviation, small commuters, corporate turbojets, T-38, C-12, C-20, C-21, T-1, fighter jets, UC-35, T-3, T-6 aircraft.

⁸Circling not authorized E of Rwy 18-36.

⁹Step Down Fix at 2 NM from thld, 1320 min.

¹⁰Step Down Fix at 2 NM from RPI, 1300 min.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

SHEPPARD AFB/WICHITA FALLS MUNI (KSPS), TX (17341 USAF)

ELEV 1019

RADAR^{1 2} - (E) Ctc SHEPPARD APP CON 118.2 269.025

T A NA when Sheppard Approach Control closed.

	RWY	GS/TCH/RPI	CAT	DH/ MDA-VIS	HAT/ HATh/ HAA	CEIL-VIS
ASR ³	15C ⁴		ABCDE	1420-¾	417	(500-¾)
	15R ⁴		ABCDE	1420-¾	422	(500-¾)
	33L ⁴		ABCDE	1440-¾	440	(500-¾)
	33C ⁵		AB	1440-¾	451	(500-¾)
			CDE	1440-¾	451	(500-¾)
C CIR ⁶	ALL RWY		A	1440-1¼	421	(500-1¼)
			B	1480-1¼	461	(500-1¼)
			C	1480-1½	461	(500-1½)
			D	2020-3	1001	(1100-3)
			E	2080-3	1061	(1100-3)

¹Sheppard APP CON clsd 0200-1200Z++ Mon-Fri, 2300-1800Z++ Sun, clsd Sat and hol, ctc FORT WORTH CENTER 133.5 350.35.

²MP ASR 0600-1200Z++ Mon-Fri.

³ASR not avbl when Sheppard APP CON is clsd.

⁴When ALS inop, increase CAT ABCDE vis to 1¼ miles.

⁵When ALS inop, increase CAT AB vis to 1¼ miles, CAT CDE vis to 1½ miles.

⁶Circling not authorized West of Rwy 15R-33L.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS