

LOC/DME I-OYC <b><u>109.5</u></b> Chan <b>32</b>	APP CRS <b>355°</b>	Rwy Idg <b>6080</b> TDZE <b>40</b> Apt Elev <b>46</b>
--	------------------------	---

ILS or LOC RWY 36  
CORPUS CHRISTI INTL (CRP)



DME required for LOC only.
----------------------------

**T** For inop ALS, increase S-ILS 36 Cat E visibility to RVR 4000 and S-LOC 36 Cat C/D/E visibility to RVR 4500.



**MISSED APPROACH:** Climb to 700 then climbing left turn to 2000 on heading 338° and on CRP VORTAC R-287 to ATHIS INT/CRP 23.3 DME and hold.

ATIS 126.8	CORPUS APP CON 120.9 348.725	CORPUS TOWER 119.4 257.8	GND CON 121.9 269.15	CLNC DEL 118.55
---------------	---------------------------------	-----------------------------	-------------------------	--------------------



700 ↑	2000 hdg 338°	CRP R-287	ATHIS △	ILS unusable inside DA. LOC unusable within 1.6 DME.				
				OSSOE I-OYC [7.2] RADAR	HADON I-OYC [13.1]		One Minute Holding Pattern	
*LOC only.								
CATEGORY	A		B		C		D	E
S-ILS 36	240/24 200 (200-½)							
S-LOC 36	340/24 300 (300-½)							
CIRCLING	500-1 454 (500-1)	580-1 534 (600-1)	820-2¼ 774 (800-2¼)	820-2½ 774 (800-2½)	820-2¾ 774 (800-2¾)			