

RNAV (GPS) RWY 13

PORT ISABEL-CAMERON COUNTY (PIL)

▼ Baro-VNAV NA when using Brownsville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. VDP NA when using Brownsville altimeter setting. When local altimeter setting not received, use Brownsville altimeter setting and increase all DA 38 feet and all MDA 40 feet, increase LPV all Cats, LNAV Cat C, and Circling Cat C visibility ¼ mile. Circling Rwy's 3, 8, 17, 21, 26, 35 NA at night.

MISSED APPROACH:
Climb to 3000 direct
COKAX and via 185°
track to CHICO and hold.

Procedure NA for arrivals at MADRE via V70 northwest bound.

(IAF) MADRE
2000 NoPT
133° (7)

4 NM

130° 310°

(IF/IAF) BUTAC

2000 NoPT
040° (5)

1600
130° (6.2)

(FAF) GEWAV

516 516

124±
RW13
172

522 508 511

549

MSA RW13 25 NM
2600

UNITED STATES

ELEV 19	TDZE 18
---------	---------

130° to RW13

COKAX

4 NM

005° 185° 85°

UNITED STATES CHICO MEXICO

4 NM Holding Pattern

BUTAC

2000

310°

130°

GP 3.00°

TCH 40°

VGS and RNAV glidepath not coincident (VGS Angle 2.00° TCH 27°)

1600

6.2 NM

2.7 NM

2.1 NM

GEWAV

*2.1 NM to RW13

RW13

*RNAV only.

CATEGORY	A	B	C	D
LPV DA	376-1¼	358 (400-1¼)		NA
RNAV/ VNAV	424-1½	406 (500-1½)		NA
RNAV MDA	480-1	462 (500-1)	480-1¼ 462 (500-1¼)	NA
CIRCLING	540-1 521 (600-1)	620-1 601 (700-1)	840-2½ 821 (900-2½)	NA