

⚠

Baro-VNAV NA when using Jackson Medgar Wiley-Evers Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Jackson Medgar Wiley-Evers Intl altimeter setting and increase all DA 19 feet and all MDA 20 feet. Increase LNAV/VNAV all Cats and LNAV Cats C/D visibilities ½ mile and Circling Cat C ¼ mile. For inop MALS R when using Jackson Medgar Wiley-Evers Intl altimeter setting increase LNAV/VNAV all Cats to 1½.

MALS R

⚠

⚠

MISSED APPROACH:
Climb to 2000 direct JILHO and hold.

ASOS 120.625	JACKSON APP CON ★ 123.9 319.2	HAWKINS TOWER ★ 119.65 (CTAF) 257.8	GND CON 121.9 239.0	CLNC DEL 121.9 (when twr closed)	UNICOM 122.95
-----------------	----------------------------------	--	------------------------	--	------------------

4 NM Holding Pattern		OCARO		2000		JILHO	
← 339°		→ 159°		← 159°		→ 339°	
GP 3.00°		TCH 56		1900		*860	
6.9 NM		3.2 NM		1.5 NM			
CATEGORY	A	B	C	D			
LPV DA		542-½	201 (300-½)				
LNAV/VNAV DA		677-⅝	336 (400-⅝)				
LNAV MDA	780-½	439 (500-½)	780-¾	439 (500-¾)			
CIRCLING	860-1 519 (600-1)	880-1 539 (600-1)	1140-2¼ 799 (800-2¼)	1320-3 979 (1000-3)			

ELEV 341

TDZE 341

159° to RWY 16

5387 X 150

0.7% UP

0.3% UP

3431 X 150

34

376

REIL Rwy 34

HIRL Rwy 16-34

MIRL Rwy 11-29

JACKSON, MISSISSIPPI

32°20'N-90°13'W

HAWKINS FIELD (HKS)

Amtd 2A 11DEC14

RNAV (GPS) RWY 16