

WAAS  
CH **56410**  
**W04A**

APP CRS  
**042°**

Rwy Idg **7505**  
TDZE **78**  
Apt Elev **79**

RNAV (GPS) RWY 4

MONROE RGNL (MLU)

RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500. Circling ASR Rwy 14 NA at night.  
\*\* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct LURBY and hold.

ATIS  
**125.05**

MONROE APP CON ★  
**118.15 290.475**

MONROE TOWER ★  
**118.9 (CTAF) 0 257.8**

GND CON  
**121.9**

CLNC DEL  
**121.65**

UNICOM  
**122.95**

CATEGORY	A	B	C	D
LPV DA **		278/24	200 (200-½)	
LNAV/ VNAV DA		383/24	305 (400-½)	
LNAV MDA	460/24	382 (400-½)	460/35	382 (400-¾)
CIRCLING	580-1	501 (600-1)	740-1¾ 661 (700-1¾)	1160-3 1081 (1100-3)

ELEV 79

TDZE 78

REIL Rwy 14 and 32

MIRL Rwy 14-32 0

HIRL Rwy 4-22 0

MONROE, LOUISIANA

Amdt 1C 08OCT20

32°31'N-92°02'W

MONROE RGNL (MLU)

RNAV (GPS) RWY 4