

| | | |
|--|------------------------|---|
| WAAS CH 61013 W30A | APP CRS 304° | Rwy Idg TDZE 10 Apt Elev 10 |
|--|------------------------|---|

RNAV (GPS) RWY 30

HOUMA-TERREBONNE (HUM)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

⚠

When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase all DA 77 feet and all MDA 80 feet, increase LPV and LNAV/VNAV all Cats, LNAV Cat C/D, and Circling Cat D visibility ¼ mile. Baro-VNAV NA when using Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH: Climb to 1800 direct NACIV and hold.

| | | | | | |
|-----------------------|--|---|---------------------------|---|-------------------------|
| ATIS 120.25 | NEW ORLEANS APP CON 118.9 350.35 | HOUMA TOWER★ 125.3 (CTAF) 0 346.3 | GND CON 123.875 | CLNC DEL 118.9 (When twr closed) | UNICOM 122.95 |
|-----------------------|--|---|---------------------------|---|-------------------------|

