WAAS CH 61308 W18A	APP CRS 179°	Rwy Idg 6500 TDZE 0 Apt Elev 0

RNAV (GPS) RWY 18

SOUTH LAFOURCHE LEONARD MILLER JR (GAO)

RNP APCH.

Rwy 18 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase all DA 77 feet and all MDA 80 feet and increase LPV all Cats visibility ¼ mile, LNAV/VNAV Cat A and B visibility ¼ mile and Cat C and D visibility ⅛ mile, LNAV Cat C and D visibility ⅜ mile and Circling Cat C and D visibility ¼ mile. Baro-VNAV and VDP NA when using Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH: Climb to 520 then climbing right turn to 2000 direct HIKEN and hold.

AWOS-3PT	NEW ORLEANS APP CON	CLNC DEL	UNICOM
118.175	120.85 256.9	120.85	123.0 (CTAF) L







CATEGORY	A	B	C	D
LPV DA	319-1	319 (400-1)		
LNAV/VNAV DA	284-⅞	284 (300-⅞)	284-1	284 (300-1)
LNAV MDA	380-1	380 (400-1)	380-1¾ 380 (400-1¾)	380-2 380 (400-2)
C CIRCLING	440-1 440 (500-1)	560-1 560 (600-1)	640-1¾ 640 (700-1¾)	640-2 640 (700-2)

SC-4, 03 DEC 2020 to 31 DEC 2020
SC-4, 03 DEC 2020 to 31 DEC 2020