

WAAS CH 99310 W18B	APP CRS 179°	Rwy Idg TDZE 55 Apt Elev 55
--	------------------------	---


RNAV (GPS) Z RWY 18

PICAYUNE MUNI (MJD)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Stennis Intl altimeter setting. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 3/4 SM NA. Procedure NA when R-4403 B, C, or E is active. When local altimeter setting not received, used Stennis Intl altimeter setting: increase LPV DA to 377 and visibility all Cats 1/8 mile; increase LNAV/VNAV DA to 621 and visibility all Cats 1/8 mile; increase all MDA 40 feet and Circling Cat C visibility 1/4 mile.

MISSED APPROACH:
Climb to 1200, then climbing right turn to 1800 direct CIQYI and hold.

AWOS-3PT 119.075	GULFPORT APP CON 124.6 354.1	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



		ELEV 55		TDZE 55	
4 NM Holding Pattern		CIQYI		ASAGE	
1800 ← 359°		179° →		1800	
GP 3.00°		TCH 36		HAPAV 3 NM to RW18	
		6.6 NM		2.4 NM	
		1.7 NM		1.3 NM	
CATEGORY		A	B	C	D
LPV DA		343-1		288 (300-1)	
LNAV/VNAV DA		587-1 7/8		532 (600-1 7/8)	
LNAV MDA		520-1	465 (500-1)	520-1 3/8	465 (500-1 3/8)
CIRCLING		520-1 465 (500-1)	580-1 525 (600-1)	700-1 3/4 645 (700-1 3/4)	960-3 905 (1000-3)

MIRL Rwy 18-36 0

5000 X 75

81

36

SC-4, 03 DEC 2020 to 31 DEC 2020

SC-4, 03 DEC 2020 to 31 DEC 2020