

WAAS CH 69216 W30A	APP CRS 296°	Rwy Idg TDZE Apt Elev	6750 12 15
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 30
JACK BROOKS RGNL (BPT)

RNP APCH.

RADAR required.

T Baro-VNAV NA when using Orange County altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). Rwy 30 helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter setting not received, use Orange County altimeter setting: increase LPV DA to 295 feet; increase LNAV/VNAV DA to 436 feet; increase all MDAs 40 feet, increase LPV and LNAV/VNAV all Cats visibility $\frac{1}{4}$ SM and LNAV Cat E visibility $\frac{1}{4}$ SM.

MISSED APPROACH:
Climb to 3000 direct
GIDDY and hold.

ATIS 126.3	HOUSTON APP CON 121.3 377.1	BEAUMONT TOWER * 119.5 (CTAF) 0	GND CON 124.85	CLNC DEL 118.3	UNICOM 122.95
----------------------	---------------------------------------	---	--------------------------	--------------------------	-------------------------

MISSED APCH FIX

MSA R1130 23 NM

3100

ELEV 15	D	TDZE 12
---------	----------	---------

□

12

BEAUMONT/PORT ARTHUR, TEXAS
Orig-A 07NOV19

29°57'N-94°01'W

JACK BROOKS RGNL (BPT)
RNAV (GPS) RWY 30

SC-5, 03 DEC 2020 to 31 DEC 2020