RNAV (GPS) RWY 22

DYERSBURG RGNL (DYR)

WAAS	APP CRS	Rwy Idg	5004
CH 86320	222°	TDZE	334
W22A		Apt Elev	338

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Blytheville Muni altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Blytheville Muni altimeter setting: increase LPV DA to 644 feet and LNAV/VNAV DA to 676 feet and all MDA 60 feet; increase LPV visibility all Cats ⅛ mile and LNAV/VNAV visibility all Cats and LNAV Cats C/D visibility ¼ mile. Night landing: Rwy 16, 34 NA.

MISSED APPROACH: Climb to 2900 direct RUQAW and hold.

AWOS-3PT	MEMPHIS CENTER	UNICOM
135.625	134.65 316.15	123.05 (CTAF)





CATEGORY	A	B	C	D
LPV DA	584-⅞ 250 (300-⅞)			
LNAV/VNAV DA	616-⅞ 282 (300-⅞)			
LNAV MDA	700-1 366 (400-1)			
CIRCLING	740-1 402 (500-1)	800-1 462 (500-1)	800-1½ 462 (500-1½)	900-2 562 (600-2)



MIRL Rwy 4-22
REIL Rwys 4 and 22

SE-1, 03 DEC 2020 to 31 DEC 2020
SE-1, 03 DEC 2020 to 31 DEC 2020