

WAAS CH 99707 W36A	APP CRS 005°	Rwy Idg TDZE Apt Elev	5003 979 979
--	------------------------	-----------------------------	---



RNAV (GPS) RWY 36

WINCHESTER MUNI (BGF)

NA DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16° C (4°F) or above 54° C (130°F). Baro-VNAV and LNAV NA when using Chattanooga altimeter setting. When local altimeter setting not received, use Chattanooga altimeter setting and increase LPV DA to 1503, LNAV/VNAV DA to 1530 and all MDA 160 feet. Increase LPV and LNAV/VNAV visibility ½ mile all Cats. Increase circling visibility ½ mile Cat C. VDP NA when using Chattanooga altimeter setting.

MISSED APPROACH:
Climb to 4000 direct ZEDUX and hold.

AWOS-3 121.675	MEMPHIS CENTER 128.15 323.125	GCO 121.725	UNICOM 122.8 (CTAF)
--------------------------	---	-----------------------	-------------------------------



CATEGORY	A	B	C	D
LPV DA	1340-1	361 (400-1)		NA
LNAV/VNAV DA	1367-1 ¼	388 (400-1 ¼)		NA
LNAV MDA	1540-1	561 (600-1)	1540-1 ½ 561 (600-1 ½)	NA
CIRCLING	1540-1	561 (600-1)	1540-1 ½ 561 (600-1 ½)	NA

