

WAAS CH 63218 W33A	APP CRS 334°	Rwy Idg TDZE Apt Elev	9001 45 46
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) Y RWY 33

CHARLESTON AFB/INTL (CHS)

RNP APCH.

▼


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C.
RVR 1800 authorized with use of FD or AP or HUD to DA.

MALS R


AS

MISSED APPROACH: Climb to 3000 direct MAMAE and hold, continue to climb-in-hold to 3000.

ATIS 124.75	CHARLESTON APP CON 120.7 306.925	CHARLESTON TOWER 126.0 239.0	GND CON 121.9 348.6	CLNC DEL 127.325 291.65	CPDLC
-----------------------	--	--	-------------------------------	-----------------------------------	-------



ELEV 46	TDZE 45
---------	---------



3000 MAMAE VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 59).				
*LNAV only.				
*1.3 NM to RW33				
SHRMP 4 NM Holding Pattern				
154° 6000 334° 3000 GP 3.00° TCH 51				
CATEGORY	A	B	C	D
LPV DA #	245/24 200 (200-½)			
LNAV/VNAV DA	472/40 427 (500-¾)			
LNAV MDA	500/24 455 (500-½)		500/45 455 (500-¾)	
CIRCLING	540-1 494 (500-1)		600-1½ 554 (600-1½) 740-2¼ 694 (700-2¼)	