

WAAS

CH 50499

W35A

APP CRS

349°

Rwy Idg

TDZE

Apt Elev

7204

31

32

RNAV (GPS) RWY 35

WILMINGTON INTL (ILM)

⚠

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALS, increase LNAV Cats C/D visibility to 1½ SM.

MALSR

MISSED APPROACH:

Climb to 3000 direct ILUXY and hold.

ATIS 124.975	WILMINGTON APP CON ★ 118.25 284.65 (164°-343°) 135.75 317.425 (344°-163°)	WILMINGTON TOWER ★ 119.9(CTAF) 0 239.3	GND CON 121.9 348.6	UNICOM 122.95
-----------------	---	---	------------------------	------------------

MISSED APCH FIX

ELEV 32

D

TDZE 31

3000 ILUXY

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	242/24 211 (300-½)			
LNAV/VNAV DA	426/45 395 (400-¾)			
LNAV MDA	500/24 469 (500-½)		500/50 469 (500-1)	
CIRCLING	560-1 528 (600-1)		720-2 688 (700-2) 920-3 888 (900-3)	

WILMINGTON, NORTH CAROLINA

Amdt 3C 17AUG17

34°16'N-77°54'W

WILMINGTON INTL (ILM)

RNAV (GPS) RWY 35