

|  |                        |   |
|--|------------------------|---|
| WAAS<br>CH <b>65937</b><br><b>W21A</b> | APP CRS<br><b>212°</b> | Rwy Idg <b>5500</b><br>TDZE <b>164</b><br>Apt Elev <b>164</b> |
|--|------------------------|---|

RNAV (GPS) RWY 21  
JOHNSTON RGNL (JNX)

**▼** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Erwin altimeter setting and increase all DA 50 feet and all MDA 60 feet; increase LPV all Cats and Circling Cat C visibility ¼ mile; increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ½ mile. Baro-VNAV and VDP NA with Erwin altimeter setting. Helicopter visibility reduction below ¾ SM NA.

**MISSED APPROACH:** Climb to 2700 direct JHDI and hold, continue climb-in-hold to 2700.

|                          |   |                       |                                   |
|--------------------------|---|-----------------------|-----------------------------------|
| AWOS-3<br><b>120.225</b> | RALEIGH APP CON<br><b>125.3 353.675</b> | GCO<br><b>135.075</b> | UNICOM<br><b>122.725 (CTAF) 0</b> |
|--------------------------|---|-----------------------|-----------------------------------|

