

RADAR INSTRUMENT APPROACH MINIMUMS


ALBEMARLE, NC  
STANLY COUNTY (VUJ)  
RADAR-1 128.325 307.8 

Orig, 22JUN17 (19059) (FAA)

ELEV 609

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	22L	3.0°/40/767	ABCD	784-¾	200	(200-¾)

Procedure NA when control tower closed.

BEAUFORT, SC  
BEAUFORT EXECUTIVE (ARW)  
RADAR-1 125.125 292.125  NA

Amdt 3A, 10MAY07 (20310) (FAA)

ELEV 10

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	25		ABC	440-1¼	430	(500-1¼)				
CIRCLING	ALL RWY		AB	500-1¼	490	(500-1¼)	C	500-1½	490	(500-1½)

Use Beaufort MCAS/Merritt Field altimeter setting.  
When Beaufort Class D not in effect, procedure NA.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

BEAUFORT MCAS (MERRITT FLD) (KNBC), Beaufort, SC

Amdt 5 18JUN20 (20254) (USN)

ELEV 37

RADAR - (E) 123.7x 298.875x 317.775x 323.275x 338.35x 372.0x 379.275x



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR <sup>1</sup>	23 <sup>2</sup>	3.0°/44/821	ABCDE	116-¾	100	(100-¾)
	5 <sup>2</sup>	3.0°/38/779	ABCDE	137-¾	100	(100-¾)
	14	3.0°/41/780	ABCDE	233-¾	200	(200-¾)
	32 <sup>8</sup>	3.0°/40/722	ABCDE	308-¾	283	(300-¾)
PAR W/O GS <sup>1</sup>	23 <sup>5 6</sup>		ABCDE	320-½	304	(300-½)
	14 <sup>6</sup>		AB	420-1	387	(400-1)
			CDE	420-1½	387	(400-1½)
	5 <sup>3 7</sup>		AB	440-¾	403	(500-¾)
			CDE	440-1	403	(500-1)
	32 <sup>6</sup>		AB	440-1	415	(500-1)
			CDE	440-1½	415	(500-1½)
ASR <sup>1 6</sup>	23 <sup>3</sup>		AB	360-½	344	(400-½)
			CDE	360-¾	344	(400-¾)
	14		AB	420-1	387	(400-1)
			CDE	420-1½	387	(400-1½)
	5 <sup>4</sup>		AB	460-¾	423	(500-¾)
			CDE	460-1	423	(500-1)
	32		AB	500-1	475	(500-1)
			CDE	500-1¾	475	(500-1¾)
CIR	5, 14, 23, 32		AB	500-1	463	(500-1)
			C	600-1½	563	(600-1½)
			D	600-2	563	(600-2)
			E	740-2½	703	(800-2½)

<sup>1</sup>No-NOTAM MP 1200-2000Z++ Sat.

<sup>2</sup>When ALS inop, increase vis CAT ABCDE to ½ mile.

<sup>3</sup>When ALS inop, increase vis CAT ABCDE to 1 mile.

<sup>4</sup>When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1¼ miles.

<sup>5</sup>When ALS inop, increase vis CAT ABCDE to 1 mile.

<sup>6</sup>VDA and VGSI not coincident.

<sup>7</sup>When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1½ miles.

<sup>8</sup>WCH for Group 4 is 16ft.

CODED LOST COMMUNICATIONS

SCARLET

**TACAN equipped aircraft:** If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand six hundred, proceed direct COSAW, execute TACAN Rwy 23 approach.

GOLD

**RNAV/GPS equipped aircraft:** If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand eight hundred, proceed direct HOWEL and execute RNAV/GPS Rwy 23 approach.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

CHERRY POINT MCAS (CUNNINGHAM FLD) (KNKT), Cherry Point, NC

Amdt 3 10SEP20 (20254) (USN)

ELEV 29

RADAR - (E) 118.35x 120.15x 275.6x 299.6x 305.2x 314.8x 320.4x 337.2x 348.0x



				DH/ MDA-VIS	HAT/ HATH/ HAA	CEIL-VIS
PAR	RWY	GS/TCH/RPI	CAT			
	32L <sup>1 3</sup>	3.0°/57/1048	ABCDE	126-¼	100	(100-¼)
	14L <sup>3</sup>	3.0°/55/1056	ABCDE	126-½	100	(100-½)
	5R <sup>3</sup>	3.0°/56/1049	ABCDE	127-½	100	(100-½)
	23R <sup>3</sup>	3.0°/57/1076	ABCDE	123-½	100	(100-½)
ASR	23R <sup>4</sup>		AB	400-½	377	(400-½)
			CDE	400-¾	377	(400-¾)
	32L <sup>2</sup>		AB	400-½	394	(400-½)
			CDE	420-¾	394	(400-¾)
	5R		AB	500-1	473	(500-1)
			CDE	500-1¾	473	(500-1¾)
	14L		AB	500-1	474	(500-1)
			CDE	500-1¾	474	(500-1¾)
CIR	ALL RWYS	AB	580-1	551	(600-1)	
		C	600-1½	571	(600-1½)	
		D	600-2	571	(600-2)	
		E	700-2½	671	(700-2½)	


<sup>1</sup>When ALS inop, increase vis CAT ABCDE to ½ mile.  
<sup>2</sup>When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1½ miles.  
<sup>3</sup>CAUTION: PAR RPI and PAPI RRP are not coincident.  
<sup>4</sup>When ALS inop, increase vis CAT ABCDE to 1 mile.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

**NEW RIVER MCAS (KNCA),** (MC CUTCHEON FLD) NC (Jacksonville) (Amdt 1, 19059 USN)  
**RADAR - (U)** 118.575 132.2 279.575 289.4 308.4 346.325 350.225 353.875  **ELEV 26**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	1 <sup>1</sup>	3.0°/45/872	ABCD	<b>124</b> -¾	100	(100-¾)
	5 <sup>5</sup>	3.0°/36/656	ABCD	<b>126</b> -½	100	(100-½)
	19 <sup>3</sup>	3.0°/40/757	ABCD	<b>123</b> -½	100	(100-½)
	23 <sup>4</sup>	3.0°/37/664	ABCD	<b>274</b> -⅙	250	(300-⅙)
PAR W/O GS	1 <sup>2</sup>		ABCD	<b>340</b> -¾	316	(400-¾)
	5		ABCD	<b>400</b> -1	374	(400-1)
	19		ABCD	<b>400</b> -1	377	(400-1)
	23		AB	<b>440</b> -1	416	(500-1)
			CD	<b>440</b> -1⅙	416	(500-1⅙)
ASR	5		ABCD	<b>400</b> -1	374	(400-1)
	23		ABCD	<b>380</b> -1	356	(400-1)
	19		AB	<b>440</b> -1	417	(500-1)
			CD	<b>440</b> -1⅙	417	(500-1⅙)
CIR	ALL RWY		AB	<b>500</b> -1	474	(500-1)
			C	<b>500</b> -1½	474	(500-1½)
			D	<b>580</b> -2	554	(600-2)

<sup>1</sup>When ALS inop, increase vis to ½ mile.  
<sup>2</sup>When ALS inop, increase vis CAT ABCD to 1 mile. The difference between the VGSI TCH (45 ft) and the procedure TCH (49 ft) is greater than 3 ft.  
<sup>3</sup>CAUTION: WCH for Group 4: 18 ft is less than the min WCH 20 ft.  
<sup>4</sup>CAUTION: WCH for Group 3: 16 ft and Group 4: 11 ft is less than the min WCH 20 ft.  
<sup>5</sup>CAUTION: WCH for Group 3: 15 ft and Group 4: 10 ft is less than the min WCH 20 ft.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

**SIMMONS AAF (KFBG)**, Fort Bragg, NC 1-Amdt 12A 2-Orig A 03DEC20  
(20338) (USA)  
**RADAR<sup>1</sup> - (E)** 120.8 124.2 257.65 284.675 **T**

ELEV 244

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
<b>RADAR-1</b>						
PAR	27	3.0°/36/628	ABC	<b>436</b> -¾	208	(200-¾)
			D	<b>NA</b>	NA	NA
PAR W/O GS	27		AB	<b>640</b> -1	412	(500-1)
			C	<b>640</b> -1¼	412	(500-1¼)
			D	<b>NA</b>	NA	NA
CIR			AB	<b>780</b> -1	536	(600-1)
			C	<b>780</b> -1½	536	(600-1½)
			D	<b>NA</b>	NA	NA
<b>RADAR-2</b>						
PAR	9	3.9°/33/487	COPTER	<b>550</b> -½	309	(400-½)

<sup>1</sup>Opr 1200-0400Z++ Mon-Fri, clsd hol. No-NOTAM preventive maint 1800-1900Z++ Fri.

**WILMINGTON, NC** Amdt 7A, 17AUG17 (17229) (FAA)  
**WILMINGTON INTL (ILM)**  
**RADAR-1** 118.25 135.75 284.65 317.425 **T A**

ELEV 32

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	24		AB	<b>500</b> /24	474	(500-½)	CD	<b>500</b> /50	474	(500-1)
	35		AB	<b>500</b> /40	469	(500-¾)	CD	<b>500</b> /50	469	(500-1)
	17		AB	<b>500</b> -1	468	(500-1)	CD	<b>500</b> -1%	468	(500-1%)
	6		AB	<b>540</b> /55	512	(600-1¼)	CD	<b>540</b> -1%	512	(600-1%)
<b>C</b> CIRCLING	ALL RWY		AB	<b>560</b> -1	528	(600-1)	C	<b>720</b> -2	688	(700-2)
			D	<b>920</b> -3	888	(900-3)				

When control tower closed, ASR NA.  
Rwy 17 helicopter visibility reduction below ¾ SM not authorized.  
For inop ALS, increase S-24 Cat C/D visibility to 1% SM, and S-35 Cats A/B visibility to RVR 5500, and Cat C/D to 1% SM.

03 DEC 2020 to 31 DEC 2020

03 DEC 2020 to 31 DEC 2020

RADAR INSTRUMENT APPROACH MINIMUMS