



DME or RADAR required		ALSF-1 		MISSED APPROACH: Climbing right turn to 3000, intercept PAM TACAN R-104 to 20 DME (SUSIE) and hold.		
▼ *When ALS inop, increase RVR to 40, vis to ¾ mile. **When ALS inop, increase RVR to 60, vis to 1 ½ miles.						
ATIS ★ 254.4	TYNDALL APP CON 125.2 392.1 (N abv 5000') 120.825 379.3 (N b/w 5000')		TYNDALL TOWER ★ 133.95 263.15	GND CON 121.9 259.3	CLNC DEL 118.05 348.7	ASR/PAR



3000	SUSIE
PAM	PAM
R-104	20

↑LOC ONLY

↑WIDIB

SELEY /RADAR

WUDOM

TACAN

JASES

3190

2100

1600

GS 2.50°

TCH 50

1.5 NM

2.3 NM

4.2 NM

6.7 NM

920 NM

15 NM

ELEV 17 TDZE 14

HIRL all Rwy  
Rwy 32L Idg 9135°

10,000 x 300

10,113 x 150

76 131 122 173 148 158

Recommend Rwy  
14L-32R for opch  
end engagemnt  
of A-Gear.

319° 5.7 NM  
from FAF

FAF to MAP 5.2 NM					
Knots	120	140	160	180	200
Min:Sec	2:36	2:14	1:57	1:44	1:34

TYNDALL AFB (KPAM)

HI-ILS or LOC Y RWY 32R