ILS or LOC/DME RWY 36

OCALA INTL-JIM TAYLOR FIELD (OCF)

LOC I-OCF	APP CRS	Rwy Idg	6347
111.5	004°	TDZE	80
		Apt Elev	89

DME from OCF VORTAC. Simultaneous reception of I-OCF and OCF DME required. When local altimeter setting not received, use Gainesville altimeter setting and increase S-ILS 36 DA to 361 and all MDA 100 feet; increase S-LOC 36 Cats C and D visibility ¼ mile. Inoperative table does not apply to S-ILS 36 all Cats when using local altimeter setting. For inoperative MALSR, increase S-LOC 36 Cats A and B visibility to 1 mile. For inoperative MALSR when using Gainesville altimeter setting, increase S-LOC 36 Cats A and B visibility to 1 mile.

MALSR

MISSED APPROACH: Climb to 3000 via OCF VORTAC R-355 to LEJKO INT/OCF VORTAC 10 DME and hold continue climb-in-hold to 3000.

ATIS	JACKSONVILLE APP CON	OCALA TOWER ★	GND CON	UNICOM
128.125	118.6 251.15	119.25 (CTAF)	121.4	123.0



ELEV 89 D TDZE 80





CATEGORY	A	B	C	D
S-ILS 36	280-¾ 200 (200-¾)			
S-LOC 36	540-¾ 460 (500-¾)			540-1 460 (500-1)
CIRCLING	580-1 491 (500-1)		580-1½ 491 (500-1½)	640-2 551 (600-2)

SE-3, 03 DEC 2020 to 31 DEC 2020
SE-3, 03 DEC 2020 to 31 DEC 2020