

WAAS CH 69604 W22A	APP CRS 225°	Rwy Idg TDZE Apt Elev	5498 242 264
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 22

THOMASVILLE RGNL (TVI)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 53°C (127°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Valdosla altimeter setting and increase LPV DA to 595, LNAV/VNAV DA to 613 and all MDA 100 feet. Increase LPV all Cats visibility to ½ SM, LNAV/VNAV all Cats visibility to 1 SM, and increase LNAV Cat C/D visibility to 1 ¼ SM. Increase Circling Cat C visibility to 2 SM and Circling Cat D visibility to 2 ¾ SM. For inop ALS, increase LPV and LNAV/VNAV all Cats visibility to ½ SM, and LNAV Cat C/D visibility to 1 ½ SM. VDP and Baro-VNAV NA when using Valdosla altimeter setting. Circling Rwy 4, 14, 32 NA at night. For inop ALS when using Valdosla altimeter setting, increase LPV all Cats visibility to 1 ½ SM, LNAV/VNAV Cat D to 1 ¼ SM and LNAV Cat C/D to 1 ¾ SM.

MALSF



MISSED APPROACH:
Climb to 700 then
climbing left turn to
2000 direct GEF
VORTAC and hold.

AWOS-3PT
119.175

VALDOSTA APP CON★
126.6 285.6

UNICOM
123.075 (CTAF) **L**

