ILS or LOC RWY 36

AUBURN UNIVERSITY RGNL (AUO)

LOC I-AUO	APP CRS	Rwy Idg	5264
110.1	005°	TDZE	759
		Apt Elev	777

When local altimeter setting not received, use Columbus altimeter setting: increase S-ILS 36 DA to 1072 feet and visibility all Cats ⅛ SM; increase all MDA 120 feet and S-LOC 36 Cats C/D visibility ¼ SM and Circling Cats C/D visibility ½ SM. For inop ALS, increase S-LOC 36 all Cats visibility ¼ SM. For inop ALS, when using Columbus altimeter setting, increase S-ILS 36 all Cats visibility to 1⅛ SM and S-LOC 36 all Cats visibility to 1⅜ SM.

MALSF

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct CSG VORTAC and hold.

AWOS-3PT	ATLANTA APP CON ★	CLNC DEL	UNICOM
132.575	125.5 323.1	118.7	123.0 (CTAF) L

ALTERNATE MISSED APCH FIX
LAGRANGE
LGC 115.6
Chan 103
R-288-108°
288°

LOCALIZER 110.1
I-AUO

MISSED APCH FIX
COLUMBUS
CSG 117.1
Chan 118
R-280-100°
280°

1243
994
1069
1380
1130
800
944

TUSKEGEE
117.3 TGE
Chan 120

2600
081°
(11.8)
R-081

2600
253°
(22.3)
R-253

COLUMBUS
117.1 CSG
Chan 118

(IAF)
AUBIE INT
TGE 11.8
CSG 22.3

005°

(CFMBX)

140°
320°
185°

MSA TGE 25 NM
2900

Remain within 10 NM
AUBIE INT
185°
2600
2600
005°
2600
GS 3.00°
TCH 44
5.7 NM

1500	3000	CSG

ELEV 777 TDZE 759

8 L
L L
4000 X 75
0.2%
26
5264 X 100
0.9% UP
36
005° 5.7 NM from FAF
MIRL Rwy 11-29 L
HIRL Rwy 18-36 L

CATEGORY	A	B	C	D
S-ILS 36	959-¾ 200 (200-¾)			
S-LOC 36	1140-¾ 381 (400-¾)		1140-1 381 (400-1)	
C CIRCLING	1280-1 503 (600-1)	1360-1 583 (600-1)	1380-1¾ 603 (700-1¾)	1480-2¼ 703 (800-2¼)

FAF to MAP 5.7 NM

Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54

SE-4, 03 DEC 2020 to 31 DEC 2020
SE-4, 03 DEC 2020 to 31 DEC 2020