

WAAS

CH **69518**

**W14A**

APP CRS

**141°**

Rwy Idg

**4999**

TDZE

**187**

Apt Elev

**187**

**RNAV (GPS) RWY 14**

HOMERVILLE (HOE)

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Waycross altimeter setting and increase all DA 59 feet and all MDA 60 feet, increase LNAV/VNAV visibility all Cats ½ mile and LNAV and Circling Cat C/D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Waycross altimeter setting.

MISSED APPROACH:  
Climb to 2000 direct ZUGSU and hold.

AWOS-3 <b>118.725</b>	VALDOSTA APP CON★ <b>126.6 285.6</b>	CTAF <b>122.9 0</b>
--------------------------	---	------------------------

Procedure NA for arrival at UPTON on V578 eastbound.

4 NM Holding Pattern

DEXBU

EDUVE

LADAW 1.7 NM to RW14

ZUGSU

2000

2000

2000

2000

GP 3.00° TCH 40

\*760

\*1 NM to RW14

\*LNAV only.

5 NM

3.9 NM

0.7 NM

1 NM

CATEGORY	A	B	C	D
LPV DA		437-1	250 (300-1)	
LNAV/VNAV DA		461-1	274 (300-1)	
LNAV MDA		560-1	373 (400-1)	
CIRCLING	680-1 493 (500-1)	740-1 553 (600-1)	940-2¼ 753 (800-2¼)	940-2½ 753 (800-2½)

MIRL Rwy 14-32 0

HOMERVILLE, GEORGIA

Amdt 1 25JUN15

31°03'N-82°46'W

HOMERVILLE (HOE)

**RNAV (GPS) RWY 14**