

WAAS
CH **86233**
W26A

APP CRS
264°

Rwy Idg
TDZE **176**
Apt Elev **176**

5004

176

176

RNAV (GPS) RWY 26

CAMILLA-MITCHELL COUNTY (CXU)

Baro-VNAV NA when using Albany altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

When local altimeter setting not received, use Albany altimeter setting and increase all DA 48 feet and all MDA 60 feet; increase visibility LPV all Cats and LNAV Cats C and D and Circling Cat C ¼ mile and LNAV/VNAV all Cats ½ mile. Helicopter visibility reduction below 1 SM NA.

Rwy 26 Straight-in and Circling minimums NA at night.

MISSED APPROACH:

Climb to 2200 direct CEGUK and hold.

AWOS-3T 118.675	JACKSONVILLE CENTER 125.75 226.8	UNICOM 122.8 (CTAF) 0
---------------------------	--	--

MSA RW26 25 NM

2600

Procedure NA for arrivals at CHULA on V578 eastbound.

2400 NoPT
225°
(20)

(IAF) CHULA

4 NM

084°

264°

(IF/IAF) CEVOR

370

580

1900

264°
(6.1)

(FAF) KUBCE

343

554

601

1542

MISSED APCH FIX

CEGUK

084°

264°

4 NM

2400 NoPT
314°
(15.9)

(IAF) WUBSU

ELEV 176

TDZE 176

2200

CEGUK

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 39).

264° to RW26

221±

5004 X 100

264°

1900

1900

5.2 NM

6.1 NM

CEVOR

4 NM Holding Pattern

084°

264°

2400

GP 3.00° TCH 58

CATEGORY	A	B	C	D
LPV DA		505-1	329 (400-1)	
LNAV/VNAV DA		553-1¼	377 (400-1¼)	
LNAV MDA	660-1	484 (500-1)	660-1⅔	484 (500-1⅔)
CIRCLING	720-1	544 (600-1)	720-1½ 544 (600-1½)	760-2 584 (600-2)

REIL Rws 8 and 26 **0**

MIRL Rwy 8-26 **0**

CAMILLA, GEORGIA

Amdt 1B 29MAY14

31°13'N-84°14'W

RNAV (GPS) RWY 26

CAMILLA-MITCHELL COUNTY (CXU)