

WAAS CH 90215 W03A	APP CRS 038°	Rwy Idg 7020 TDZE 3652 Apt Elev 3661
--	------------------------	---

RNAV (GPS) RWY 3

LEA COUNTY RGNL (HOB)

	<p>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 52°C (126°F). DME/DME-RNP-0.3 NA. When local altimeter setting not received, use Carlsbad altimeter setting and increase all DA 281 feet and all MDA 300 feet, increase LPV and LNAV/VNAV all Cats visibility ½ mile, LNAV Cats C/D visibility ¾ mile, Circling Cat C visibility ¾ mile, and Circling Cat D visibility ½ mile. Baro-VNAV and VDP NA when using Carlsbad altimeter setting. Inoperative table does not apply to LPV and LNAV/VNAV. For inoperative MALSR increase LNAV Cats C/D visibility to 1 mile. For inoperative MALSR when using Carlsbad altimeter setting, increase LPV and LNAV/VNAV all Cats visibility to 1¾ miles, and LNAV Cats C/D to 1½ miles. Rwy 17 helicopter visibility reduction below 1 SM NA. Circling Rwy 17 NA at night.</p>	<p>MALSR</p>	<p>MISSED APPROACH: Climb to 6000 direct DEKEC and hold.</p>
--	--	--------------	---

MALS



MISSED APPROACH:
Climb to 6000 direct
DEKEC and hold.

ATIS 119.75	FORT WORTH CENTER 133.1 298.95	HOBBS TOWER ★ 120.65 (CTAF) 0 317.4	GND CON 121.9	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------

